



























| | Blizzard A320 | Blizzard A330 Pro | Blizzard A335-S Pro | Blizzard A350 Pro | Blizzard A355 Pro | Blizzard A380 Pro | Blizzard A385-S Pro Zoom |
|-------------------------------|----------------------------|------------------------------|------------------------------|-----------------------------|-----------------------------|------------------------------|-------------------------------|
| Online preis | € 49,95 | € 59,95 | TBD | € 99,95 | € 129,00 | € 219,00 | TBD |
| Aktive Array-Größe | FHD (1920*1080) 30fps | FHD (1920*1080) 30fps | FHD (1920*1080) 30fps | QHD (2592*1944) 30fps | QHD (2592*1944) 30fps | UHD 4K3840*2160 30fps | UHD 4K3840*2160 30fps |
| Energiebedarf | 100mA bei 1920*1080 30fps | 100mA bei 1920*1080 30fps | 100mA bei 1920*1080 30fps | 300mA @ 2592*1944 30fps | 300mA @ 2592*1944 30fps | 400 mA bei 3840*2160 30 fps | 400 mA bei 3840*2160 30 fps |
| Sensorgöße | 1/2,7-Zoll-CMOS-Sensor | 1/2,5-Zoll-CMOS-Sensor | 1/2,9-Zoll-CMOS-Sensor | 1/2,5-Zoll-CMOS-Sensor | 1/2,8 Zoll CMOS Sensor | 1/2,8-Zoll CMOS Sensor | 1/2,3 Inch CMOS Sensor |
| Sensor model | JX-F22 Silicon-Optronic | JX-F23 Silicon Optronics | imx323 (Sony) | PS5520 PrimeSensor | Sony335 | IMX415 Sony (8.5 MP) | imx378 Sony |
| MAX SNR | ≥38dB | ≥37dB | ≥37dB | ≥39dB | ≥39dB | ≥41dB | ≥41dB |
| Empfindlichkeit | 3900 mv/lux-sec | 3300 mv/lux-sec | 3300 mv/lux-sec | 2400 mv/lux-sec | 2400 mv/lux-sec | 2400 mv/lux-sec | 2400 mv/lux-sec |
| AEC/Gewinn/Weiß-Bilanz | 6500K | 5500K | 5500K | 5500K | 5500K | Automatisch (2800-7000K) | Automatisch (2800-7000K) |
| Maximale Bildübertragungsrate | FHD 30 fps | FHD 30 fps | FHD 30 fps | QHD 30 fps | QHD 30 fps | QHD 30 fps | QHD 30 fps |
| Objektivgröße | 14mm | 14mm | 14mm | 14mm | 14mm | 18mm | 6,8mm |
| Fokusslänge | 3mm (distortion-less lens) | 3mm (distortion-less lens) | 3mm (distortion-less lens) | 3mm (distortion-less lens) | 3mm (distortion-less lens) | 7.5mm (distortion-less lens) | 4,74mm (distortion-less lens) |
| Zoom | Nein | Nein | Nein | Nein | Nein | Nein | Ja (5x) |
| Diagonales Sichtfeld | 75 Grad | 90 Grad | 93 Grad | 90 Grad | 90 Grad | 112 Grad | 65/78.5/90 Grad |
| WDR-Technologie | Nein | Nein | Ja (21-43dB) | ≥95dB | ≥75dB | Nein | Ja (0-72dB) |
| Anzahl der Mikrofone | 1 (mono) | 1 (mono) | 2 (stereo) Analog | 2 (stereo) | 2 (stereo) Analog | 2 (stereo) Analog | 2 (stereo) Analog |
| Betriebstemperatur (Umgebung) | -10°C bis +60° C | -10°C bis +60° C | -10°C bis +60° C | -10°C bis + 60° C | -10°C bis + 60° C | -10°C bis + 60° C | -10°C bis + 60° C |
| Abmessungen | 105mm*25mm*46mm | 150mm*30mm*55mm | 150mm*30mm*55mm | 150mm*30mm*55mm | 150mm*30mm*55mm | 150mm*30mm*55mm | 150mm*30mm*55mm |
| Schnittstelle | USB Type-A | USB Type-C | USB Type-C | USB Type-C | USB Type-C | USB Type-C | USB Type-C |
| USB Kabel | Fixes USB Type-A | USB Type-C - USB Type-A 1.5m | USB Type-C - USB Type-A 1.5m | USB Type-C - USB Tpe-A 1.5m | USB Type-C - USB Tpe-A 1.5m | USB Type-C - USB Type-A 1.5m | USB Type-C - USB Type-A 1.5m |

Feature spotlight

| | | | | | | |
|--|---|--|--|--|--|--|
|  |  |  |  |  |  |  |
|  USB Type A |  USB Type-C |  USB Type-C |  USB Type-C |  USB Type-C |  USB Type-C |  USB Type-C |
|  PLUG & PLAY |  PLUG & PLAY |  PLUG & PLAY |  PLUG & PLAY |  PLUG & PLAY |  PLUG & PLAY |  PLUG & PLAY |
| | |  Analog | |  Analog |  Analog |  Analog |
| | | | | | |  5X ZOOM |